

GB6-24 / GB10-24

FIRE ALARM BELLS



Standard Features

- 24 VDC
- Available in 6" or 10" housing
- High dBA output
- Mounts to a standard 4" square electrical box
- ANSI/UL listed for outdoor use when used with the GBBB back box
- 18 AWG wire leads
- Available in red metal finish

Product Overview

The GB Series provide durable and dependable operation required for life safety alarm systems.

Alarm bells are low current, high decibel notification appliances for use in fire and burglary systems or other signaling applications.

The GB Series is available in 6" or 10" housing and listed for indoor and outdoor applications. Bells must be used with the GBBB box for outdoor use.

The GB Series is ANSI/UL 464 listed and the units are warranted for 3 years from the date of purchase.

Technical Specifications

| | |
|-------------------------------|---|
| Indoor Operating Temperature | 32° to 120°F (0° to 49°C) |
| Outdoor Operating Temperature | -31° to 150°F (-35° to 65.6°C) |
| Operating Temperature | -30°F (-35 °C) ~ 150°F (66°C) |
| Current Draw (both models) | 100mA |
| Sound Output | GB6-24: 95dBA @ 10ft. GB10-24: 96dBA @ 10ft. |

Ordering Codes

| | |
|----------------|--|
| GB6-24 | Fire Alarm Bell 24VDC 6" - Red |
| GB10-24 | Wall Mount Low Profile Evacuation Horn White Faceplate |
| GBBB | Backbox for outdoor mounting |